



BEARING CORP.OF CANADA LTD.

3.347 Inch | 85.014 Millimeter x 1.25 in x 13.000
in TIMKEN FSAF 22217 Pillow Block Bearings



Bearing No. FSAF 22217

FSAF 22217 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	19.52
EAN	0087796074934
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Shaft Mount
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22217
Seals	Triple Ring Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Inch
Other Features	Double Row Straight Bore
Long Description	4 Bolt Pillow Block; 3.347" Bore; 3-3/4" Base to Center Height; Shaft Mount Mount; Spherical Roller Bearing; 9-7/8" Minimum Bolt Spacing; 11" Bolt Spacing Maximum; Relubricatable;



BEARING CORP.OF CANADA LTD.

Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	FSAF 22217
Weight / LBS	43
B	3.75 Inch 95.25 Millimeter
Bolt Spacing Maximum	11 Inch 279.4 Millimeter
D	4.938 Inch 125.425 Millimeter
d	3.347 Inch 85.014 Millimeter
Bolt Spacing Minimum	9.875 Inch 250.83 Millimeter
Nominal Bolt Center to Center	10.4 Inch 264.2 Millimeter
Actual Bolt Center to Center	0 Inch 0 Millimeter
Diameter S-2	3 15/16 in
Diameter S-3	3 3/16 in
A	3.75 in
B	13.000 in
C	3.500 in
D	1.25 in
E Max.	11.0000 in
E Min.	9.8750 in
F	2.125 in
H ¹	7.250 in
Oil Level K	1.4375 in
L ²	4.938 in
Y	1.4219 in
No. of Base Bolts Required	4



BEARING CORP.OF CANADA LTD.

Size of Base Bolts Required	5.8 in
Locknut	AN17
Lockwasher	W17
Housing Only ³	FSAF217
Bolt Hole Length	1.1875 in
Bolt Hole Width	0.625 in
Stabilizing Ring 1 Req ' d ⁴	SR-17-14
Triple Seal 2 Req ' d at S-2	LOR89
Triple Seal 2 Req ' d at S-3	LOR63
Assembly Weight	43 lb
Full Timken Part Number	FSAF22217
Seal Type	Triple Ring Seal